



CRYOTECH BX36[®]

Liquid Runway Deicer

Safety Data Sheet

Section 1: IDENTIFICATION

PRODUCT IDENTIFIER

CRYOTECH BX36[®] Liquid Runway Deicer
With DuPont Tate & Lyle Susterra[®] propanediol
Complies with Specification AMS 1435

RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Deicing/anti-icing runways, taxiways, and airside pavements

DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Name/Address: Cryotech Deicing Technology
6103 Orthoway
Fort Madison, IA 52627
United States

Contact Information: Telephone: (800) 346-7237
Fax: (319) 372-2662
Email: deicers@cryotech.com
Website: www.cryotech.com

EMERGENCY TELEPHONE NUMBER

CHEMTREC (800) 424-9300
Outside continental USA (703) 527-3887

Section 2: HAZARD(S) IDENTIFICATION

CLASSIFICATION ACCORDING TO OSHA HAZCOM 2012

Hazard Class Not classified as hazardous

LABEL ELEMENTS ACCORDING TO OSHA HAZCOM 2012

There are no OSHA required label elements for this product.

CLASSIFICATION ACCORDING TO WHMIS (Canada)

Hazard Class Not controlled

WHMIS Hazard Symbols Not applicable

WHMIS Signal Word Not applicable

POTENTIAL HEALTH EFFECTS

Eye Contact May cause temporary eye irritation. Corneal injury is unlikely.

Skin Contact Repeated contact may cause slight skin irritation or dry skin.

Inhalation May cause irritation or coughing.

Ingestion Ingestion of large quantities may cause nausea, vomiting, diarrhea and abdominal discomfort.

Effects of repeated exposure No effects other than described above are expected.



CRYOTECH BX36[®]

Liquid Runway Deicer

Safety Data Sheet

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

MIXTURES

Ingredient	CAS No	Wt. %
Cryotech BX36 [®] Liquid Runway Deicer Aqueous solution containing:		100
Susterra [®] Propanediol	504-63-2	0-50
Potassium Acetate	127-08-2	0-50
Corrosion inhibitors		< 1%

Section 4: FIRST- AID MEASURES

DESCRIPTION OF FIRST AID MEASURE

Eye	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, seek medical attention.
Skin	As a precaution, wash skin thoroughly with soap and water. Remove and wash contaminated clothing.
Inhalation	If inhaled, remove to fresh air and get medical advice
Ingestion	If swallowed, give milk or water to drink and telephone for medical advice. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

MOST IMPORTANT SYMPTOMS / EFFECTS

Eye	May cause eye irritation. Symptoms may include temporary discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Skin	May cause itching or irritation of any cut or abraded skin. Symptoms of prolonged contact may include dry skin.
Inhalation	Inhalation of aerosol during spraying may cause respiratory tract irritation and coughing. This product is not otherwise expected to be an inhalation hazard.
Ingestion	Ingestion of large quantities may cause nausea, vomiting, diarrhea and abdominal discomfort.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT

Note to physicians	This product contains potassium acetate. Though ingestion of large amounts of potassium salts usually results in vomiting, excessive potassium absorption can cause hyperkalemia.
---------------------------	---



CRYOTECH BX36[®]

Liquid Runway Deicer

Safety Data Sheet

Specific treatments If you feel unwell, seek medical advice immediately. Show the label or safety data sheet to medical personnel if possible.

Section 5: FIRE FIGHTING MEASURES

FLAMMABILITY

Flash Point (close cup) >100°C (212°F)
Auto Ignition No data available

EXTINGUISHING MEDIA

Suitable Extinguishing Media Water, carbon dioxide, or dry chemical. Use extinguishing media appropriate for surrounding materials.
Unsuitable Extinguishing Media Not applicable

SPECIAL HAZARDS

Hazardous Combustion Products Normal combustion forms carbon dioxide and water.
Explosion Limits Data not available. Not considered to be an explosion hazard.
Unusual Fire Hazards This product may become combustible after prolonged heating.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIREFIGHTERS

Special Protective Equipment for Firefighters Wear NIOSH approved self-contained breathing apparatus (SCBA) with positive air pressure.

Section 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES

Avoid eye/skin contact with spilled material. Refer to Section 7 for additional handling precautions

Methods for Containment Contain and/or absorb spill with inert material (e.g. sawdust, sand, vermiculite).
Methods for Cleaning-Up Scoop up material and transfer to disposal container. Wash the spillage area with plenty of water. If needed, wash spillage area with plenty of water.

Section 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

Handling Avoid eye contact. Avoid breathing mist when spraying.

PRECAUTIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage Store in tightly sealed original containers, away from direct heat and strong oxidizing agents. Do not store or handle product in systems constructed of wetted parts consisting of galvanized steel, zinc, or brass components.



CRYOTECH BX36[®]

Liquid Runway Deicer

Safety Data Sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS

Exposure Limits

No specific limits have been established for this product.

EXPOSURE CONTROLS

Engineering Controls

No special ventilation is usually necessary; however if operating conditions create high airborne concentrations of this material, special ventilation may be needed to keep exposure to airborne contaminants below the exposure limit.

INDIVIDUAL PROTECTIVE MEASURES/PERSONAL PROTECTIVE EQUIPMENT

Eye Protection

Safety glasses or goggles are recommended if splashing/spraying is possible.

Skin Protection

No special skin protection is usually necessary. Chemical-resistant gloves and clothing should be used if prolonged exposure is possible to prevent drying of skin.

Respiratory Protection

No special respiratory protection is usually necessary. Breathing of mist/aerosol should be avoided. If operating conditions create high airborne concentrations of this material, the use of an approved respirator is recommended.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Clear, colorless to light straw colored liquid. (May be dyed blue at customer request.)
ODOR	Odorless to slight vinegar odor
ODOR THRESHOLD	No data available
pH (20°C, 68°F)	10.5 – 11.5
FREEZING POINT	-45°C (-50°F)
BOILING POINT	~113°C (236°F)
FLASH POINT	>200°F
EVAPORATION RATE	No data available
FLAMMABILITY/EXPLOSION LIMITS	Not applicable
VAPOR PRESSURE (20°C)	No data available
VAPOR DENSITY (AIR = 1)	No data available
RELATIVE DENSITY	1.16
SOLUBILITY IN WATER	Completely miscible
PARTITION COEFFICIENT; n-OCTANOL/WATER	No data available
AUTO-IGNITION TEMPERATURE	No data available
DECOMPOSITION TEMPERATURE	No data available
VISCOSITY (20°C)	10 cP
OXIDIZING PROPERTIES	Not oxidizing
EXPLOSIVE PROPERTIES	Not explosive



CRYOTECH BX36[®]

Liquid Runway Deicer

Safety Data Sheet

Section 10: STABILITY AND REACTIVITY

REACTIVITY

No dangerous reactions known under conditions of normal use.

CHEMICAL STABILITY

Stable. Polymerization will not occur.

POSSIBILITY OF HAZARDOUS REACTIONS

No dangerous reactions known under conditions of normal use.

CONDITIONS TO AVOID

Avoid prolonged contact with reactive metals such as magnesium and zinc, especially in closed systems where hydrogen gas from the oxidation of these materials may accumulate over time.

INCOMPATIBLE MATERIALS

Strong oxidizing agents; strong acids.

HAZARDOUS DECOMPOSITION PRODUCTS

May decompose into oxides of carbon.

Section 11: TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

LD50 rat-oral: > 5 g/kg (estimated from studies of components)

LIKELY ROUTES OF EXPOSURE

Skin contact, eye contact, ingestion.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL, AND TOXICOLOGICAL CHARACTERISTICS

Eye	May cause eye irritation. Symptoms may include temporary discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Skin	May cause itching or irritation of any cut or abraded skin. Symptoms of prolonged contact may include dry skin.
Inhalation	Inhalation of aerosol during spraying may cause respiratory tract irritation and coughing. This product is not otherwise expected to be an inhalation hazard.
Ingestion	Ingestion of large quantities may cause nausea, vomiting, diarrhea and abdominal discomfort.

DELAYED AND IMMEDIATE EFFECTS AND CHRONIC EFFECTS FROM SHORT- AND LONG-TERM EXPOSURE/NUMERICAL MEASURES OF TOXICITY

Skin Corrosion/Irritation	Based on available data, the classification criteria are not met.
Serious Eye Damage/Irritation	Based on available data, the classification criteria are not met.
Respiratory or Skin Sensitization	Based on available data, the classification criteria are not met.
Germ Cell Mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	This product does not contain any ingredients that are considered to be carcinogens by IARC, NTP, or OSHA.



CRYOTECH BX36[®]

Liquid Runway Deicer

Safety Data Sheet

Reproductive Toxicity	Based on available data, the classification criteria are not met.
STOT-Single Exposure	Based on available data, the classification criteria are not met.
STOT-Repeated Exposure	Based on available data, the classification criteria are not met.
Aspiration Hazard	Based on available data, the classification criteria are not met.

Section 12: ECOLOGICAL INFORMATION

ECOTOXICITY (AQUATIC AND TERRESTRIAL)

Not expected to cause long-term adverse effects in the aquatic or terrestrial environments.

PERSISTENCE AND DEGRADABILITY

Readily biodegradable. COD (TOD): 0.60 g O₂/g deicer; BOD₅ (20°C): 0.37 g O₂/g deicer

BIOACCUMULATIVE POTENTIAL

Bioaccumulation is not expected.

MOBILITY IN SOIL

Adverse effects not expected.

OTHER ADVERSE EFFECTS

None expected.

Section 13: DISPOSAL CONSIDERATIONS

WASTE TREATMENT AND METHODS OF DISPOSAL

Based on available information, this product is neither listed as a hazardous waste nor does it exhibit any of the characteristics that would cause it to be classified as a characterized hazardous waste under RCRA. This product may be absorbed onto suitable materials and disposed of in a sanitary landfill unless local, state, or provincial regulations prohibit such disposal.

Section 14: TRANSPORT INFORMATION

TRANSPORT INFORMATION

Not regulated as dangerous goods per US DOT or IATA.

Section 15: REGULATORY INFORMATION

INVENTORY LISTS

All of the components in this product are on the following inventory lists: USA (TSCA), Canada (DSL/NDL); Europe (EINECS)

TSCA SECTION 12(b)

None of the chemicals in this product are listed under TSCA Section 12(b).

CERCLA HAZARDOUS SUBSTANCES

There is no CERCLA Reportable Quantity for this material.



CRYOTECH BX36[®]

Liquid Runway Deicer

Safety Data Sheet

SARA 311 CATEGORIES

Immediate (Acute) Health Hazard:	No
Delayed (Chronic) Health Hazard:	No
Fire Hazard:	No
Sudden Release of Pressure Hazard:	No
Reactivity Hazard:	No

SARA 313

None of the components in this product are subject to reporting under SARA Section 313.

CLEAN WATER ACT

None of the chemicals in this product are listed as Priority Pollutants under the CWA.

None of the chemicals in this product are listed as Toxic Pollutants under the CWA.

STATE RIGHT-TO-KNOW:

This product does not contain components at levels which are required to be reported under the statutes of the following states: PA, MA, MN, and NJ.

This product does not contain materials known to the State of California (Proposition 65) to cause cancer and/or reproductive harm at levels which would require a warning under the statute.

NFPA 704	
Health	1
Fire	0
Physical Hazard	0
Hazard Rating 0-4 0-least hazardous; 4-most hazardous	

HMIS – Hazardous Materials Identification System	
Health	1
Fire	0
Physical Hazard	0
Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = serious, 4 = severe	

Section 16: OTHER INFORMATION

SDS REVISION DATE

Revision date: October 21, 2015

Expiration date: October 21, 2018

Latest version of this SDS can be obtained from Cryotech.

NOTE TO EMPLOYER

This Safety Data Sheet contains environmental, health and toxicology information for your employees. Please ensure this information is provided to them. It also contains information to help you meet community right-to-know/emergency response reporting requirements under SARA Title III and many other laws. If you resell this product, this SDS must be given to the buyer or the information incorporated in your SDS. Discard any previous edition of this SDS.



CRYOTECH BX36[®]

Liquid Runway Deicer

Safety Data Sheet

DISCLAIMER

The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use or misuse are beyond our control, GENERAL ATOMICS INTERNATIONAL SERVICES CORPORATION dba Cryotech Deicing Technology makes no warranty, either express or implied, with respect to the completeness or continuing accuracy of the information contained herein and disclaims all liability for reliance thereon. GENERAL ATOMICS INTERNATIONAL SERVICES CORPORATION dba Cryotech Deicing Technology assumes no responsibility for any injury or loss resulting from the use of the product described herein. User should satisfy himself that he has all current data relevant to his particular use.

End of Safety Data Sheet